

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>G06F 3/00, G06K 11/18, G09B 9/28</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 95/32459</b> <b>(43) International Publication Date:</b> 30 November 1995 (30.11.95)
<b>(21) International Application Number:</b> PCT/US95/06204 <b>(22) International Filing Date:</b> 19 May 1995 (19.05.95) <b>(30) Priority Data:</b> 08/245,957 19 May 1994 (19.05.94) US <b>(71) Applicant:</b> EXOS, INC. [US/US]; 2A Gill Street, Woburn, MA 01801 (US). <b>(72) Inventors:</b> MARCUS, Beth, A.; 78 Woburn Street, Lexington, MA 02173 (US). OSBORNE, Timothy; 10 Udine Street, Arlington, MA 02174 (US). AN, Bin; Apartment 2, 21 Newport Street, Arlington, MA 02174 (US). EBERMAN, Brian; 264 Willow Avenue, Somerville, MA 02144 (US). <b>(74) Agent:</b> PASTERNAK, Sam; Choate, Hall & Stewart, Exchange Place, 53 State Street, Boston, MA 02109 (US).		<b>(81) Designated States:</b> AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SI, SK, TJ, TT, UA, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ, UG).  <b>Published</b> <i>With international search report.</i>
<b>(54) Title:</b> INTERACTIVE SIMULATION SYSTEM INCLUDING FORCE FEEDBACK INPUT DEVICE  <b>(57) Abstract</b>  Interactive simulation including force feedback. The system includes a computer game display unit programmed with simulation rules. A control unit is connected to the computer and provides information and control signals to the computer to interact with the stored simulation rules and to receive information and control signals from the computer. A movable structure for movement in at least two degrees-of-freedom by an operator is interconnected to the control unit by means of actuators. A programmable unit processes signals and information from the computer to generate signals to drive the actuators so as to apply forces in the at least two degrees-of-freedom to the movable structure and thereby to the operator. The applied forces are based on internal programming within the programmable unit, events occurring in the simulation and movements of and forces applied to the movable structure by the operator. The system of the invention thereby provides continuous interaction among motion of and forces applied by the movable structure, the events in the simulation and forces applied to and applied by the movable structure.		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

## INTERACTIVE SIMULATION SYSTEM INCLUDING FORCE FEEDBACK INPUT DEVICE

**Background of the Invention**

5 This invention relates to interactive simulations, and more particularly to simulations and games including force or touch feedback to a joystick or multi-axis controller or input device.

Interactive computer simulations and interactive video games often include a movable structure generally known as a joystick to provide inputs for the simulation or game. Oftentimes, the joystick is strictly an input  
10 device by which signals are conveyed to the processing unit of the computer. These joysticks do not provide any tactile or force feedback to the user.

The Atari Hard Drivin<sup>®</sup> video game provides one-dimensional force feedback to a steering wheel or a brake pedal. That is, during a game, torques are generated on the steering wheel which simulate those torques  
15 which would be experienced during, for example, cornering in a car. See also, U.S. Patent No. 5,044,956. In a more general simulation context, control elements including force feedback are known in elaborate flight simulators costing many millions of dollars. Heretofore, there has been no multiple-degree-of-freedom joystick suitable for games and simulations and  
20 suitable for arcade and home use.

**Summary of the Invention**

The interactive simulation system of the invention includes a computer or game display unit programmed with simulation rules. A  
25 control unit is connected to the computer and provides information and control signals to the computer to interact with the stored simulation rules and to receive information and control signals from the computer. A movable structure for movement in at least two degrees-of-freedom by an operator is interconnected to the control unit by means of actuators. A  
30 programmable unit processes signals and information from the computer to generate signals to drive the actuators so as to apply forces in the at least

two degrees-of-freedom to the movable structure and thereby to the operator. The applied forces are based on internal programming within the programmable unit, events occurring in the simulation and movements of and forces applied to the movable structure by the operator. The system  
5 thereby provides continuous interaction among motion of and forces applied by the movable structure, the events in the simulation and forces applied to and applied by the movable structure.

In a preferred embodiment the simulation system is an interactive video game and the programmable unit resides in the control unit. In this  
10 embodiment, the movable structure is a joystick with two degrees-of-freedom. The actuators include electric motors driving a low-friction, low-backlash transmission. The programmable unit includes integrated electronics for controlling feedback and modeling user interaction with the simulation or game. It is also preferred that information compression  
15 technology be used so that much smaller information sets can be processed and communicated while still achieving a desired experience.

By providing touch or force feedback, the system of the invention more effectively involves the operator in the simulation or game. For example, in two-dimensional games such as flight simulators the present  
20 touch feedback is used to allow the player to feel the difference in performance between a small general aviation airplane and a high performance military fighter and to feel environmental forces such as air turbulence or updrafts. In this case the joystick, known as a PowerStick™, will feel a variety of programmable effects including feeling "stiffer" or  
25 "softer" depending on which type of airplane is being "flown" by the simulation user. In three-dimensional games (which are just now becoming available) force feedback is particularly valuable because navigating in a three-dimensional environment is often difficult and the touch feedback provided by the invention will enable the user to feel objects which are  
30 being encountered and provide a real-time indication of where an object

controlled by the user or player is. In games involving contact, such as fighting games, the invention simulates and displays to the operator's hand the feel of collisions with objects encountered during the game or simulation and interaction with terrains of different textures.

5

### **Brief Description of the Drawing**

Fig. 1 is a block diagram illustrating the overall system of the invention.

10 Fig. 2 is a plan view, with parts broken away, of the force feedback control unit of the invention.

Figs. 3 and 4 are side and front cross-sectional views, respectively, of the joystick control unit of the invention.

15 Fig. 5 is a cross-sectional view of an alternative embodiment of the invention.

Fig. 6 is a bottom view of the embodiment of Fig. 5.

Fig. 7 is a detail taken from Fig. 5.

Fig. 8 is a detail taken from Fig. 6.

20 Fig. 9 is a block diagram of the signal and communication paths in the operation of the invention.

Figs. 10 and 11 are perspective illustrations of a character in an interactive game with force feedback according to the invention.

### **Description of the Preferred Embodiment**

25 The overall system of the invention is illustrated schematically in Fig.

1. A control unit 10 includes a movable structure such as a joystick 12.

The control unit 10 also includes a programmable section 14. It will be appreciated that the unit 14 need not be a part of the control unit 10; it could be separate or part of the computer 16. A general purpose digital computer

30 16 such as a personal computer or game display unit is programmed with

simulation or game rules. The output from the computer 16 is displayed on a video monitor 18. The control unit 10 is connected to the computer 16 and provides information and control signals to the computer 16 to interact with the stored simulation rules and to receive information and control  
5 signals from the computer 16. The programmable unit 14 processes signals and information from the computer 16 and generates inputs to, and processes outputs from the joystick 12.

With reference now to Fig. 2, the control unit 10 supports the movable structure or joystick 12 for two degrees-of-freedom motion with  
10 respect to the control unit 10. The joystick 12 also includes at least one button type switch 20 for sending signals to the computer 16.

With reference now to Figs. 3 and 4, the control unit 10 is shown without its cover. The control unit 10 includes electric motors 30 and 32 along with angular rotation sensors 34 and 36. The motors 30 and 32  
15 include shafts bearing capstans 38 and 40. The sensor 34 responds to the angular orientation of capstan 38 and the sensor 36 responds to the angular orientation of the capstan 40 to generate signals for use by the programmable unit 14. A cable transmission mechanism driven by the capstan 38 is adapted to rotate the joystick 12 about an axis 42, that is, left  
20 and right in Fig. 3. Similarly, the capstan 40 is adapted to rotate the joystick 12 about an axis 44 so that it moves into and out of the plane of Fig. 3. As shown in Fig. 4, a drum 46 cooperates with the capstan 38 to effect rotation. This transmission system has low backlash and low friction. The sensors 34 and 36 provide an output proportional to angular orientation  
25 of the respective motor 30 and 32 shafts.

As shown in Fig. 1, the control unit 10 is connected to the computer 16 so that information and control signals can pass in either direction between the control unit 10 and the computer 16. The programmable unit 14 may be included in the control unit 10 housing or may be part of the  
30 computer 16 itself. The programmable unit 14 processes signals from the

computer 16 using internally stored rules and equations to generate signals to drive the motors 30 and 32 so as to produce forces with two degrees of freedom to the joystick 12 and to a user (not shown) operating the joystick 12. The applied forces are based on internal programming within the programmable unit 14, events occurring in the simulation and movements of and forces applied to the joystick 12 by an operator (not shown). The system therefore provides continuous interaction among motion of the joystick 12, events in the simulation and the forces applied to and applied by the joystick 12.

10 With reference now to Figs. 5, 6, 7 and 8, another embodiment of the control unit 10 is described. A motor 50 through a linkage denoted generally at 52 rotates a shaft 54. The shaft 54 passes through an angular orientation sensor such as potentiometer or encoder 56. The shaft 54 causes a bracket 58 to move left and right in Fig. 6 and engages a lower portion 59 of the joystick 12 to cause the joystick 12 to move left and right in Fig. 5. The slotted bracket 58 is supported in bearings 60 and 61.

15 Similarly, a motor 62 drives a linkage 64 which rotates a shaft 68 which passes through a potentiometer or encoder 70. The shaft 68 causes a bracket 72 to rotate as shown in Fig. 6 to cause the joystick 12 to move into and out of the plane of Fig. 5. The bracket 72 is supported by bearings 73 and 74.

20 As will be appreciated, as the motors 50 and 62 are energized, the joystick 12 is driven with two degrees-of-freedom, that is, left and right and in and out of the plane of Fig. 5. The rotational sensors 56 and 70 provide electrical outputs proportional to the angular orientation of their respective shafts. With reference to Fig. 5, the programmable unit 14 is shown as a circuit board 76 which may include the motor control and signal processing electronics.

25 With reference now to Fig. 9 the programmable unit 14 includes a microcontroller 80 which communicates with the computer 16 (Fig. 1)

through a host connection 82. The microcontroller 80 is any suitable processor such as a digital signal processor (DSP) or RISC architecture processor for enhanced operation. Further, the system can be designed for an upgradable processor core, independent of I/O hardware. In addition, the possibility exists of changing the controller's executable code from the host computer. This flexibility opens up the opportunity to customize the operation of the device for specific host applications. The microcontroller 80 executes boot code upon start up that loads in default operating firmware from on-board non-volatile memory (or removable media, e.g., memory cards) and waits for a host command to begin execution, or to download operational software. The default operation code provides general force feedback, positional, and other functions. Code downloaded to the microcontroller 80 from the host computer 16 can be tuned for specific functions and/or characteristics. The downloaded code can either be native executable binary or pseudocode for an on-board interpreter. An interpreter implementation removes the need for the host to know what processor resides on the control unit. Amplifiers 84 and 86 drive the motors 30 and 32 in the embodiment of Fig. 3 or the motors 50 and 62 in the embodiment of Fig. 6. It is to be noted that currents in the drive motors can be used to determine torque which can also be inferred from strain gauges or other types of force/torque sensors (not shown) on drive cables or shafts. It should also be noted that the torque transmission can be a four-bar linkage as illustrated in Figs. 5 and 6, a cable transmission illustrated in Figs. 3 or 4 or a belt or gear train. If desired for a particular application, a speed reduction can be built into the transmission to amplify the torque applied to the joystick 12. In applications where space and motor size are not constrained, the motors 50 and 62 can be directly mounted onto shafts 54 and 68 in Fig. 6 without transmissions.

An example of a game or simulation illustrating the technology of the



invention disclosed herein will now be described in conjunction with Figs. 10 and 11. The system of the invention has been integrated into an IBM Windows demonstration game which itself does not form a part of this invention. In this exemplary game, a character 90 fights his way through a series of different terrains to reach a treasure (not shown). The walking, running, jumping, squatting, punching and kicking of the character 90 are controlled by movements of the joystick 12. When, for example, the character 90 hits a patch of ice, the force being felt by the player goes to zero and can in fact use the motion and forces applied by the operator to further exaggerate the effect by actively getting out of the way of the operator to simulate sliding. On rough terrain, vibrations and pulses are felt by the game player in proportion to the objects encountered. If the character 90 is jumping and hits a tree or other object, the player will feel the stiffness of the object through forces transmitted through the joystick 12. When the button 20 is depressed, the character 90 stops moving and kicks or punches as shown in Fig. 11. Depending on the nature of the object being punched or kicked, and also depending on other events in the game, the forces experienced by the player will be different. Also, the velocity of the motions change the forces felt as they would in real fighting. Real physical models of the environment and objects encountered are programmed into the programmable unit 14 so that feedback is virtually instantaneous and independent of the graphics update of the computer 16. This architecture also makes the game fully interactive in which game outcomes unanticipated by the programmers occur based on the performance of the player. Because of the force feedback, the player is more actively involved in the game since the forces applied to the joystick 12 realistically simulate forces which would be felt by the character 50 in the game.

What is claimed is:

## Claims

1. Interactive simulation system comprising:
  - a computer programmed with simulation rules;
  - a control unit connected to the computer and adapted to provide information and control signals to the computer to interact with the stored simulation rules and to receive information and control signals from the computer;
  - a moveable structure adapted to be moved with at least two degrees-of-freedom by an operator and interconnected to the control unit through actuators; and
  - programmable means for processing signals from the computer to generate signals to drive the actuators to apply force and touch feedback in the at least two degrees-of-freedom to the moveable structure and to the operator, the applied forces based on internal programming within the programmable means, events occurring in the simulation and movements of and forces applied to the moveable structure by the operator, whereby there is continuous interaction among motion of the moveable structure, the events in the simulation and forces applied to and applied by the moveable structure.
2. The interactive simulation system of claim 1 wherein the programmable means is included with the control unit.
3. The interactive simulation system wherein the actuators comprise:
  - at least two motors for generating forces about respective axes of rotation.

4. The interactive simulation system of claim 1 wherein the actuators include at least one cable drive.



5. The interactive simulation system of claim 1 wherein the actuators include a four-bar linkage.

6. The interactive simulation system of claim 1 wherein the actuators include electrical motors and each motor includes means for determining angular orientation of the motor shaft.

7. The interactive simulation system of claim 1 wherein the programmable means is located apart from the control unit.

8. The interactive simulation system comprising:  
a computer programmed with simulation rules;  
a control unit connected to the computer and adapted to provide information and control signals to the computer to interact with the stored simulation rules and to receive information and control signals from the computer;  
a movable structure adapted to be gripped and moved by an operator in two degrees-of-freedom and interconnected to the control unit by means of electric motors and a transmission; and  
programmable means associated with the control unit for processing signals from the computer to generate signals to drive the motors to apply forces in the two degrees-of-freedom to the movable structure and to the operator, the applied forces based on internal programming within the programmable means, events occurring in the simulation and movements of and forces applied to the movable structure by the operator, whereby there is continuous interaction among motion of the movable structure, the events in the simulation and forces applied to and applied by the movable structure.

9. Control unit for interacting with a computer, comprising:
  - a movable structure adapted to be moved with at least two degrees-of-freedom by an operator;
  - actuators adapted to apply force and touch feedback to the movable structure with at least two degrees-of-freedom; and
  - programmable circuitry for processing information to generate signals to drive the actuators to apply force and touch feedback in the at least two degrees-of-freedom to the movable structure and to an operator.



2/6




FIG. 3




FIG. 4

3 / 6




FIG. 5




FIG. 6

SUBSTITUTE SHEET (RULE 26)

4/6




FIG. 7




FIG. 8



5/6




FIG. 9

6/6




FIG. 10




FIG. 11

SUBSTITUTE SHEET (RULE 26)

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 95/06204

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 G06F3/00 G06K11/18 G09B9/28

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G06F G09B G06K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US,A,3 919 691 (A. MICHAEL NOLL) 11 November 1975 see the whole document ---	1-9
X	EP,A,0 489 469 (ENGEL, FREDERICK LOUIS) 10 June 1992 see the whole document ---	1-3,8,9
Y	---	4-7
X	FR,A,1 102 320 (M. RICHARD CARL DEHME) 19 October 1955 see the whole document -----	1-3,8,9
Y	---	4-7

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

28 August 1995

Date of mailing of the international search report

11.09.95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Cervantes, J

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 95/06204

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A-3919691	11-11-75	NONE	
EP-A-0489469	10-06-92	NL-A- 9002669 JP-A- 4291414	01-07-92 15-10-92
FR-A-1102320	19-10-55	NONE	